

Equipment Control Failure

Class Bib No Country	Competitors Name
Boat Specifications: Boat Length (minimum)	K1 C1 C2 Comments 3.50m 3.50m 4.10m
Boat Width (minimum)	0.6m
Boat Weight (minimum)	9 Kgs 9 Kgs 15 Kgs
Extra weight permanently attached	
Boat Ends: (minimum)	ı
Horizontal: 2cm;	Bow Stern
Vertical: 1cm;	Bow Stern
Rails Moulded in End Radius >4mm	Height < Wider than 20mm 8mm
Handles Material used at least 6mm diameter or 2 x 10mm cross section Easy insertion of entire hand up to base of thumb	30cm (maximum) from bow 30cm (maximum) from stern
Buoyancy Jacket	'
Buoyancy Jacket floats 6.12Kg	
Buoyancy Jacket carries visible ISO or US Coas markings	st Guard ISO US Coast 12402- Guard Type 5 111
Buoyancy Jacket is on the ICF list of registered equipment	
No evidence of modification to the buoyancy jack	ket
Safety Helmet	
Safety Helmet Carries visible EN 1385 marking	Visible date of Manufacture
Visible designation "Helmet for Canoeing and Whitewater sports Safety helmet is on the ICF list of registered	Mark or name of Manufacturer visible
equipment No evidence of modification to the Safety Helmet	
No evidence of modification to the Salety Hellilet	
Signature – Equipment Controller	Signature – Team Leader
Please Print Name	L Please Print Name