



**ICF Paracanoe
BOAT STANDARDS
(Rev. February 22, 2011(4))**

General Notes:

1. Modifications are permitted for stability if the boat is made slower. (ie. stabilizing pontoons)
2. Adaptation equipment is not regulated. It is included as part of the weight of the boat if it is securely attached.

K-1

Maximum Length	520 cm.
Minimum Width	50 cm. (measured 10cm from the bottom of the hull)
Minimum Weight	12 kg.

K-2

Maximum Length	650 cm.
Minimum Width	47 cm. (measured 10cm from the bottom of the hull)
Minimum Weight	18 kg.

V-1

Maximum Length	730 cm
Minimum Weight	13 kg.

V-1 Ama (pontoon)

Maximum Length	See note 1 below
----------------	------------------

V-2

Maximum Length	850cm
Minimum Weight	18 kg.

V-2 Ama (pontoon)

Maximum Length	See note 1 below
----------------	------------------

Va'a Notes:

1. The va'a shall be a single hull va'a, rigged with a single ama (outrigger pontoon) and double 'iako (spreaders), separated by at least one (1) seat.
2. A.) The hull, ama and 'iako must meet the specifications set forth above.
B) When the event host is not providing a set of identical V1 or V2 for the event, the hull, ama and 'iako must meet the specifications set forth above.

3. Para Va'a equipment such as a support seat must be removable. The paddler may supply his/her own equipment as approved by the IVF Para Va'a Committee Chair.
4. Either sit-in or sit-on-top va'a may be used; however, the sit-in va'a is recommended.
5. The ama will be attached on the left side, but must be able to be attached on the right side to accommodate paddler needs as approved by the IVF Para Va'a Committee Chair.
6. Rudders are not permitted.