



ICF Paracanoe BOAT STANDARDS

(February, 2012 - FINAL)

General Notes:

1. Modifications are permitted for stability if the boat is made slower. (ie. stabilizing pontoons)
2. Adaptation equipment is not regulated. It is included as part of the weight of the boat if it is securely attached.

K-1

Maximum Length	520 cm.
Minimum Width	50 cm. (measured 10cm from the bottom of the hull)
Minimum Weight	12 kg.

K-2

Maximum Length	650 cm.
Minimum Width	47 cm. (measured 10cm from the bottom of the hull)
Minimum Weight	18 kg.

V-1

Maximum Length	730 cm
Minimum Weight	10 kg. (Excluding ama & iako)

V-1 Ama (outrigger)

Maximum Length	See note 1 below
----------------	------------------

V-2

Maximum Length	850cm
Minimum Weight	14 kg. (Excluding ama & iako)

V-2 Ama (outrigger)

Maximum Length	See note 1 below
----------------	------------------

Va'a Notes:

1. The va'a shall be a single hull va'a, rigged with a single ama (outrigger) and double 'iako (spreaders), separated by at least one (1) seat.



2. When the event host is not providing a set of identical V1's or V2's for the event; the hull, ama and 'iako must meet the specifications set forth above.
3. Specialized and personal Para Va'a equipment such as a support seat must not damage boats and must be easily removable only when using borrowed boats. This provision is to prevent delays in the competition.
4. The ama will be attached on the left side, but may be able to be attached on the right side to accommodate paddler needs as approved by the IVF Para Va'a Committee Chair or the ICF Paracanoe Technical Official.
5. Rudders, skegs and projecting keels are not permitted.
6. The Va'a hulls may be convex or concave.